

ESCORT

LCR METER

132C



Discover the tremendous value with a range of features that help this meter provide the precise measurements you need

This meter will accurately measure capacitors, inductors and resistors using the test frequencies of 100Hz, 120Hz 1 kHz, 10kHz and 100kHz. The dual display will simultaneously display the associated quality factor, dissipation or phase angle value using a series or parallel equivalent circuit. This meter is shipped fully tested and calibrated and, with proper use, will provide years of reliable service

Product Features

- ✓ Frequency Range: 100Hz, 120Hz, 1kHz, 10kHz, 40kHz, 100kHz;
- ✓ Supports Electrolytic Capacitance Measurement;
- ✓ Automatic Recognition of Component Measurement;
- ✓ Support screening and deviation measurement;
- ✓ 2.8-inch TFT display, 4-bit semi-display;
- ✓ USB communication interface; Supports SCPI
- ✓ Large capacity lithium battery power supply;
- ✓ Adjustable measuring speed, manual and automatic range;
- ✓ Short circuit correction with open circuit;
- ✓ Provides multiple test ports.
- ✓ Provide system settings: configure language, buzzer, screen brightness and so on according to user requirements

Specifications

Model	132C
Test frequency	100Hz,120Hz,1KHz,10KHz,40kHz,100KHz
Basic accuracy	0.30%
Display	2.8-inch TFT LCD
Display digit	Main parameters: 5 bits, secondary parameters: 5 bits
Measurement parameters	Main parameters: L/C/R/Z, sub-parameters: X/D/Q/theta/ESR
Electrolytic capacitor mode	YES
Measuring range	L: 0.000 μ H ~ 2000H, C: 0.000pF ~ 20.000mF, R: 0.0001 Ω ~ 20.00M Ω
Measurement display speed	1/s (slow), 2/s (medium), 4/s (fast)
Test level	0.6Vrms
Calibration function	Open circuit calibration and short circuit calibration
Screening function	The limit range of screening can be set to 1%-50%, of which the fixed points are 1%, 5%, 10%, 20%.
Deviation measurement	Used to compare the percentage of deviation between the component and the nominal value set and display
Other	Adjust backlight brightness, automatic shutdown time can be set, Chinese and English optional, USB Device communication

Standard accessories:

- ✧ Mini-USB data Wires;
- ✧ Power adapter;
- ✧ Short circuit chip;
- ✧ Red & black rubber plug;
- ✧ Large capacity lithium battery

Optional accessories:

- ✧ Kelvin test clip;
- ✧ SMD testing clamp

ESCORT

ESCORT INSTRUMENTS CORPORATION

NO.6, Alley 6m Lane 45m Pao-Hsin Road, Taipei, Taiwan

Tel: (02) 913-1326-8, Fax: 886-2-9183929