

SERIES 130-C - 130 kN

MAIN CHARACTERISTICS PP130-C - HPI130-C - API130-C

COMPRESSION SECTION	max. 400 mm ²
MAXIMUM STROKE	30 mm

COMPRESSION FORCE	130 kN
OPERATING PRESSURE	700 bar (70 MPa)

HEAD OPENING: 29 mm



PP130-C – Hydraulic Crimping Head

The unit must be operated through 700 bar hydraulic pump to reach compression force of 130 kN. (pages 77 - 84)

Technical Characteristics:

- Sturdy and compact structure
- C head for easy positioning of dies
- Quick make snap lock connection and non detachable dust cap

Tool dimensions: 128 x 254 x 78 mm
Tool weight: 4,1 kg

Description	Order No.	Dimensions	Weight
Set crimping head	PP130-C	400 x 350 x 130 mm	5,6 kg

Set Equipment:

- Hydraulic Crimping Head
- Plastic case for crimping head and 14 crimping dies



HPI130-C – Hand Operated Hydraulic Crimping Tool

Technical Characteristics:

- Sturdy and compact structure
- Snap closure crimping head, rotates 270°
- Quick feed with double hydraulic cylinder
- Single hand use by innerside handle
- Automatic pressure safety valve
- Manual return at any position by turning the main handle

Tool dimensions: 222 x 561 x 78 mm
Tool weight: 6,6 kg

Description	Order No.	Dimensions	Weight
Set crimping tool	HPI130-C	700 x 260 x 105 mm	8,2 kg

Set Equipment:

- Test Report
- Manual crimping tool
- Plastic case for crimping tool and 9 crimping dies