

GPS-8815F

DC Resistance Tester with fully automated real-time detection controlled by a high-performance microprocessor

The GPS-8815F DC resistance meter is ideally suited for measuring contact resistance of relays, switches, and PCB traces, typically outside the resistance range of multimeters. The 8815F is equipped with an intuitive front panel complete with a keypad and a vivid 5-inch colour touch screen. The touch screen and keys both provide a convenient interface for setting parameters quickly and precisely. Additionally, it supports fast cycle times for production automation and includes a BIN comparator function.

The 8815F allows measurement of low resistivity materials with offset voltage compensation to reduce the influence of thermal EMF. The temperature compensation function corrects for ambient temperature changes that cause different resistance measurements of the same component.



Key Features

- Maximum measuring current: 10A
- Measuring range: 0.01μΩ to 20MΩ
- 5-inch colour touch screen
- Temperature measurement with correction
- Manual or auto ranging
- 5^{4/5} digit display
- Bi-directional current test and pulse test method to avoid the test loop heat affecting test accuracy
- BIN comparator function
- Standard RS232, USB and LAN interfaces for data communication and remote control
- Screen capture to USB drive

Applications

- electrical testing
- circuit maintenance
- component verification
- heater industry
- transformer industry
- and many more...

www.gpslimited.com/8815F
 For all enquiries, Tel: +44 (0) 208 964 3600
 Email: info@gpslimited.com

Technical Specifications

DC Resistance Tester	
Model	GPS-8815F
Parameter	DC resistance
Accuracy	0.01% +/- 3 digits
Measurement range	0.01μΩ to 20MΩ
Signal source	Maximum current: < 10A Current mode: pulse current, positive/negative current
Range	6 ranges manual and automatic
Speed	Adjustable: 10 times/sec or 1 time/sec
Result display	Show / ΔABS / Δ% and result sorting
Max display	500'000 counts
Calibration	Open circuit and short circuit reset
Trigger	Internal, Manual, External
Temperature compensation	Accuracy: 0.2 Range: 0~80
Test terminal	4 terminal test
Comparator	Upper limit/ lower limit / close the comparator
Interface	RS232/RS485/LAN/USB communication port/USB flash drive port
Screen	5-inch colour touch screen
Other functions	Keypad lock and data hold function

Standard Accessories

Kelvin clip test cable
Temperature probe
RS232 communication cable

Optional Accessories

4-terminal clamp fixture

Power Supply

90-250VAC 50/60Hz

Power Consumption

Max. 15VA

General Specifications

Part Numbers / Optional Accessories		
Code	Item	Part Number
GPS-8815F	High Precision DC Resistance Meter (Ohmmeter)	628815

Mass

2.75kg/6.0lbs approx.

Dimension

Main unit: 300(L)×264(W)×107(H)mm

Operating

Temp -10°C to 50°, humidity RH<85%

Storage

Temp -15°C to 55°, humidity RH<90%

Services

1-year warranty (subject to product registration with GPS Ltd)
Please contact for more information.

www.gpslimited.com/8815F
For all enquiries, Tel: +44 (0) 208 964 3600
Email: info@gpslimited.com